



Report Number: 19-003009

Revision Number:1

Date Order Received: 06/03/2019

For the Account of: Pierre Frey Inc.

1692 Chantilly Drive NE

Suite C

Atlanta, GA 30324

Client's Identification:	F3405 - Ramier
--------------------------	----------------

CERTIFICATE OF TESTING

TEST PERFORMED: NFPA 260 Standard Methods of Tests and Classification System for Cigarette Ignition Resistance of Components of Upholstered Furniture – 2013; Fabric Cover Test and UFAC Fabric Classification Test Method – 1990; Standard Test Methods for Cigarette Ignition Resistance of Components of Upholstered Furniture ASTM E 1353-16 – Cover Fabric Test

TEST RESULTS

Specimen	Char Length (in)
1	0.9
2	0.6
3	0.7

NOTES

Test Conditions: 70 ±4°F, 65 ±5% Relative Humidity

Dev-009: Used SRM 1196 Equivalent YES

Lot # 18390120015

ACCEPTANCE CRITERIA

- 1. If the test specimen has no ignition, or if no individual specimen yields a vertical char of 45 mm (1.75 in; ASTM states 1.8 in.) or less, the fabric is classified a Class I cover fabric.
- 2. If the vertical char of the test specimen greater than 45 mm (1.75 in.; ASTM states 1.8 in), the fabric is classified a Class II cover
- 3. If an obvious ignition of the polyurethane substrate occurs on the test assembly, the fabric is classified a Class II cover fabric.

CONCLUSION	ONCLUSION Based on the above Results and Acceptance Criteria, the item tested is:		
	☑ Class I		
	☐ Class II		
	I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment tandard stated above.		
Berta Sti	ver		

Authorized Signature

Date Order Completed: 06/11/2019